PRODUCT NAME/VISCOSITIES:

PERFORMANCE BRAKE FLUID DOT 5.1

Product No	7977
Issue No.	2
Issue Date	04/01/17

DESCRIPTION:

A long life fluid for all types of hydraulic actuated brake and clutch systems requiring this specification. The product is highly suitable for anti-lock brake (ABS) systems.

APPLICATION:

Specially designed for anti-lock braking systems. Also suitable and miscible with DOT 3, DOT 4 and DOT 5.1 non silicone based products.

Note: Do not mix with DOT 5 silicone based products.

USER BENEFITS:

- High wet boiling point provides a long life performance fluid.
- Miscible with DOT 3, DOT 4 and DOT 5.1 non silicone based products.
- The low viscosity ensures excellent fluid circulation through valves and anti-lock systems.
- Excellent seal compatibility and anti-corrosion properties.

PERFORMANCE PROFILE:

- SAE J 1703, J 1704
- ISO 4925 (Classes 3, 4 & 5.1
- US FMVSS 116 DOT 5.1, DOT 4, DOT 3

TYPICAL CHARACTERISTICS:

Dry Boiling Point	272°C
Wet Boiling Point	185°C
Appearance	Pale Straw

HEALTH AND SAFETY:

Health and Safety Data Sheet 7977 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk