PC & LCV

MILLERS OILS

PRODUCT DATA SHEET

Product No	7742
Issue No.	1
Issue Date	14/05/2018

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF DCT-DSG

DESCRIPTION:

Premium fully synthetic automatic transmission fluid.

APPLICATION:

For use in Dual Clutch Transmission gearboxes, DSG or DCT wet clutch applications.

USER BENEFITS:

- Dual Clutch Transmissions offer improved fuel consumption and require a product specifically designed for this purpose.
- Excellent oxidation and thermal stability and low temperature pumpability provide a stable long life product.
- Improved anti-wear and resistance to sludge extends component life.

PERFORMANCE PROFILE:

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

- VW Group TL 052 182, VW TL 052 529
- Porsche Oil No. 999.917.080.00
- BMW (Getrag) 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 147 477
- MB 236.21 (001 989 85 03) MB 236.25
- Peugeot/Citroen 9734.S2
- Ford (Getrag) M2C936-A
- Mitsubishi MZ320065 Dia-Queen SSTF-1
- Volvo 1161838, 1161839
- Wet clutch applications using FFL2, FFL3, FFL5 fluids

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.856
Kinematic Viscosity @ 100°C	7.4cSt
Kinematic Viscosity @ 40°C	36.8cSt
VI	172
Pour Point °C	-51
Flashpoint °C	198
Brookfield Viscosity@-40□C	15,000cP
Appearance	Undyed

Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk

MILLERS OILS

PRODUCT DATA SHEET

HEALTH AND SAFETY:

Health and Safety Data Sheet 7742 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk