



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES: MILLERMATIC ATF UN

Product No	5386
Issue No.	2
Issue Date	18/03/13

DESCRIPTION:

An automatic transmission and power steering fluid.

APPLICATION:

For use in automatic transmission and power steering systems as recommended by the vehicle manufacturer.

USER BENEFITS:

- Will provide a high performance in accordance with vehicle manufacturer requirements.
- Very high resistance to oxidation and degradation in use and so suitable for use where very long service intervals are required.
- Ensures a smooth transmission of power.

PERFORMANCE PROFILE:

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

- General Motors Dexron IID
- Ford Mercon M2C 138CJ, M2C 166H, M2C 185A
- MB 236.1, 236.5, 236.6, 236.7
- ZF TE-ML-02F, 04D, 09B, 11A, 11B, 14A, 17C

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.866
Kinematic Viscosity @ 100°C	7.5cSt
Kinematic Viscosity @ 40°C	38.9cSt
Viscosity Index	164
Pour Point °C	-42
Flashpoint °C	210
Brookfield Viscosity @ -40°C	34,000cP
Colour	Red

HEALTH AND SAFETY:

Health and Safety Data Sheet 5386 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk